

MATERIAL SAFETY DATA SHEET

Page 1 of 4

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME: ISO TAMER FOAM

MANUFACTURER'S NAME:

INNOVATIVE STYLING OPTIONS, INC.

EMERGENCY #: (800) 584-8038 - 24 hours

INFORMATION #: (203) 656-7859 (8:30 am– 5:00 pm)

ADDRESS (NUMBER, STREET, CITY, STATE, & ZIP CODE):

110 TOKENEKE ROAD,
DARIEN, CT 06820

PREPARED: 5/02/2005

CURRENT MSDS UPDATE:

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME(S)	CAS NUMBER	TLV-TWA	PEL
Mixture of Propane/Isobutane		1000 ppm	UNK

SECTION 3. HAZARDS IDENTIFICATION

Physical/chemical hazards: The data available do not support any physical or chemical hazard.
Human health hazards: The data available do not support any adverse human health hazard.
Environmental hazards: The data available do not support any environmental hazard.

SECTION 4. FIRST-AID MEASURES

Effects and symptoms

Inhalation: No specific effects and/or symptoms have been reported or known.

Ingestion: No specific effects and/or symptoms have been reported or known.

Skin contact: Prolonged or repeated exposure may be irritating (redness, pain).

Eye contact: Prolonged or repeated exposure may be irritating (redness, tears and pain).

First-aid measures

Inhalation: None Known.

MATERIAL SAFETY DATA SHEET

Page 2 of 4

Ingestion: Product is not likely to be ingested. If this occurs, treat symptomatically. Never give anything by mouth to an unconscious person. Call a physician.

Skin contact: Remove contaminated clothing. Wash off with plenty of water and soap.

Eye contact: Avoid spraying in eyes. Accidental introduction into eye can result into moderate irritation. Immediately wash out with plenty of water with the eyelid held wide open for at least 15 minutes. Consult a doctor in the event of any complaints.

Protection of first-aiders: Avoid exposure. Use appropriate protection (see section 8).

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable: All types of extinguishing agent permitted. Dike fire control water for later disposal.

Special fire-fighting procedures: Since all pressurized aerosol cans may explode when exposed to excessive heat protect from excessive heat with water spray.

Protection of fire-fighters: Burning may produce: toxic and/or corrosive vapours/gases. Wear suitable protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Flammable. Do not use near flame or while smoking.

Environmental precautions: Leaking cans should be placed in open containers outdoors from any source of ignition, until all pressure has been released.

Methods for cleaning up: Seal leak if possible without risk. Prevent dispersion. Collect spilled material in sealable containers. Wash away remainder with plenty of water.

SECTION 7. HANDLING AND STORAGE

WARNING: Contents under pressure. Do not puncture or incinerate.

Handling: When handling the product, allow for materials and conditions which should be avoided (see Section 10). Avoid contact with skin and eyes.

Specific use(s): Not available.

Storage: Store in dry area at normal temperatures. Avoid storing at high temperature or near heat source. Avoid freezing temperatures.

Packaging materials

Suitable: Not available.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering measures: Ventilation recommended.

Hygiene measures: When using do not eat, drink or smoke. Follow good housekeeping

MATERIAL SAFETY DATA SHEET

Page 3 of 4

practices.

Personal Protective Equipment

Respiratory system: With sufficient ventilation, extraction or closed system, breathing apparatus not necessary.

Other protective equipment: Not available.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Dense foam
Color:	White
Odor:	Fragranced
Molecular weight:	N/A
Boiling point:	N/A
Melting point:	N/A
Density:	1.1 - 2.1
Vapour density (air=1):	N/A
Vapor pressure :	Can pressure not to exceed 139 psig @ 131°F (55°C)
Specific gravity (H2O=1):	1.010 – 1.025
Solubility in water:	Soluble
Octanol/water partition:	N/A
pH:	4.0 – 5.0
Flash point:	N/A
Explosion properties:	Containers may rupture and release flammable liquids and/or gases if exposed to heat of fire.

SECTION 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.
Conditions to avoid: Do not store containers in direct sunlight or where conditions will heat them above 120 F (50 C).

Hazardous Reactions: Not available.

Chemical Incompatibility: Do not mix with strong oxidizers

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity: N/A

Dermal: Repeated exposure may cause skin dryness or cracking.

Eye irritation: Direct contact of product with eyes may cause irritation, and may result in irreversible damage.

SECTION 12. ECOLOGICAL INFORMATION

